

Boat Manufactured By:



PO Box 1899 • Cairo, GA
(229) 377-2125

www.sailfishboats.com

SAILFISH® 290 CC

Length	28' 6"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	5,050 lbs
Maximum HP	600 hp
Fuel Capacity	240 gal
Weight as Tested	7,315 lbs

F300XCA / LF300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™-SD5™
Diameter x Pitch	15 1/4 x 19
Yamaha Part #	6CE-45970-00-00 / 6CF-45970-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	60° F / 65° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 1/4 tank of fuel, 3 batteries, safety and test gear.

YPB#: PB_SLF_290CC_t_F300XCA_2013-12-12_OCC



Engine: Yamaha F300XCA / LF300XCA

Boat: Sailfish® 290 CC

Configuration: Twin

Test Date: 12-Dec-2013



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6	2.7	2.22
1500	8.7	4.3	2.02
2000	12	6.7	1.79
2500	21	9.7	2.17
3000	28.7	12.9	2.23
3500	34.2	16.8	2.04
4000	39	21.8	1.79
4500	43	27.6	1.56
5000	47.6	33.4	1.43
5500	53.4	44	1.21
6000	58.2	53.2	1.09
Time to Plane: 3.17			
0-30 MPH: 4.41			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.