

Boat Manufactured By:

Premier Pontoons

PO Box 509 • Wyoming, MN 55092
(651) 462-2880

www.pontoons.com

PREMIER® 290 GRAND VIEW PTX

Length	29' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,700 lbs
Maximum HP	350 hp
Fuel Capacity	47 gal
Pontoons (#/Diameter)	3 / 36 PTX Center - 25 Outside
Weight as Tested	5,070 lbs

F300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™-SD5™
Diameter x Pitch	15 1/4 x 15
Yamaha Part #	6CE-45976-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	79° F / 73° F
Elevation (in feet above sea level)	675'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 2 batteries, safety and test gear.

YPB#: PB_PRM_290GrandViewPTX_F300XCA_2014-08-02_PNT



Engine: Yamaha F300XCA

Boat: Premier® 290 Grand View PTX

Configuration: Single

Test Date: 2-Aug-2014



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5	1.2	4.17
1500	7.3	2.2	3.32
2000	10.4	3.3	3.15
2500	15	4.7	3.19
3000	19.5	6.1	3.2
3500	23.8	8.1	2.94
4000	26.7	11.2	2.38
4500	30	14.8	2.03
5000	35.1	19.7	1.78
5500	38.5	24.4	1.58
5800	40.6	25.7	1.58
0-30 MPH: 4.92			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.