



PERFORMANCE BULLETIN

Engine: Yamaha VF250LA

Boat: Pathfinder® 2300

HPS®

Configuration: Single

Test Date: 4-Jan-2011




PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.3	1.5	4.2
1500	8.1	2.7	3
2000	9.2	3.8	2.42
2500	18.7	5	3.74
3000	31.6	6.6	4.79
3500	38	9.3	4.09
4000	43.7	12.5	3.5
4500	49.9	16.3	3.06
5000	54.9	18.9	2.91
5500	61.7	22.8	2.71
6050	63.7	23.3	2.73

Seconds to Plane: 2.87

Seconds 0-30 MPH: 6.55



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



PATHFINDER® 2300 HPS®

Length	23' 6"
Beam	8' 4"
Dry Weight (Boat Mfr. Pub)	2,495 lbs
Maximum HP	300 hp
Fuel Capacity	60 gal
Weight as Tested	3,835 lbs

VF250LA

Horsepower	250 hp
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1 on Jackplate
------------------------	-----------------

PROPELLER(S)

Series	High Seas 4-Blade Series
Diameter x Pitch	15 x 23
Yamaha Part #	6BR-45B74-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	70° F / 75° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 25 gallons of fuel, 4 batteries, T-top, 6" Atlas jack plate, optional leaning post w/livewell, bow-mounted trolling motor, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with GPS receiver. Other speed data gathered with GPS receiver.

YPB#: PB_PAT_2300HPS_VF250LA_2011-01-04_BAY

Boat Manufactured By:

Pathfinder
3207 Industrial 29th Street • Ft. Pierce, FL 34946
(772) 465-0631

www.pathfinderboats.com

(<http://www.pathfinderboats.com>)

PATHFINDER
ANGLER DRIVEN