

Boat Manufactured By:



1750 Signal Point Road, Ste. 9B • Charleston, SC 29412

(843) 708-0755

www.freemanboatworks.com

FREEMAN® 34VH

Length	33' 7"
Beam	10' 10"
Dry Weight (Boat Mfr. Pub)	7,440 lbs
Maximum HP	900 hp
Fuel Capacity	400 gal
Weight as Tested	11,010 lbs

F350UCB / LF350UCB

Horsepower	350 hp
Induction	EFI
Displacement	5.3 L
Weight (Estimated)	780 lbs
Gear Ratio	1.73

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Ventilation Plate Height	1 1/2" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series XL*
Diameter x Pitch	15 1/4 x 21
Yamaha Part #	6AW-45976-10-00 / 6AX-45976-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	70° F / 65° F
Elevation (in feet above sea level)	0'
Wind Velocity	15-20 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 4 batteries, optional hard top, safety and test gear.

YPB#: PB_FRE_34VH_t_F350UCB_2015-03-12_OCC-CAT



Engine: Yamaha F350UCB / LF350UCB

Boat: Freeman® 34VH

Configuration: Twin

Test Date: 12-Mar-2015



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	3.2	1.78
1500	8.3	6.1	1.36
2000	10.5	10.2	1.03
2500	19.2	14.4	1.33
3000	28	17.9	1.56
3500	35.8	22.6	1.58
4000	42	27.1	1.55
4500	45.9	33.2	1.38
5000	54.4	39.6	1.37
5500	61	53	1.15
6050	66.8	68.2	0.98
Time to Plane: 4.23			
0-30 MPH: 7.26			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.