

Boat Manufactured By:



PO Box 1899 • Cairo, GA
(229) 377-2125

www.sailfishboats.com

SAILFISH® 320 CC

Length	31' 6"
Beam	10' 0"
Dry Weight (Boat Mfr. Pub)	7,200 lbs
Maximum HP	600 hp
Fuel Capacity	285 gal
Weight as Tested	10,010 lbs

F300UCA / LF300UCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	575 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™-SDS™
Diameter x Pitch	15 1/4 x 18
Yamaha Part #	6CE-45934-00-00 / 6CF-45934-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 76° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 150 gallons of fuel, 3 batteries, T-top, leaning post, safety and test gear.

YPB#: PB_SLF_320CC_t_F300UCA_2014-10-31_OCC



Engine: Yamaha F300UCA / LF300UCA

Boat: Sailfish® 320 CC

Configuration: Twin

Test Date: 31-Oct-2014



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6	2.5	2.4
1500	7.5	4.4	1.71
2000	9.1	6.9	1.32
2500	15.7	10.1	1.56
3000	22.8	13.1	1.74
3500	30.4	16.8	1.81
4000	35.4	22.2	1.6
4500	40	29.5	1.36
5000	44.4	35.3	1.26
5500	47.9	45	1.06
6050	54.5	51.9	1.05
Time to Plane: 3.25			
0-30 MPH: 6.35			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.