



PERFORMANCE BULLETIN

Engine: Yamaha VF250LA


Boat: Skeeter® ZX 250

Configuration: Single

Test Date: 24-Aug-2014



PERFORMANCE DATA



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



SKEETER® ZX 250

| | |
|----------------------------|-----------|
| Length | 20' 11" |
| Beam | 7' 11" |
| Dry Weight (Boat Mfr. Pub) | 2,085 lbs |
| Maximum HP | 250 hp |
| Fuel Capacity | 44 gal |
| Weight as Tested | 3,460 lbs |

VF250LA

| | |
|--------------------|---------|
| Horsepower | 250 hp |
| Induction | EFI |
| Displacement | 4.2 L |
| Weight (Estimated) | 505 lbs |
| Gear Ratio | 1.75 |

ENGINE MOUNTING HEIGHT

| | |
|------------------------|--------|
| Mounting Hole Position | #3 |
| Jack Plate | Manual |

PROPELLER(S)

| | |
|--------------------|--------------------------|
| Series | VMAX® Ventless Series |
| Diameter x Pitch | 15 1/8 x 25 |
| Yamaha Part # | 6CB-45972-00-00 |
| Propeller Material | Polished Stainless Steel |

TEST CONDITIONS

| | |
|--------------------------------------|---------------|
| Number of People | 2 |
| Air / Water Temperature (Fahrenheit) | 73° F / 88° F |
| Elevation (in feet above sea level) | 230' |
| Wind Velocity | 0-5 MPH |

COMMENTS

Test weight includes 22 gallons of fuel, 4 batteries, bow-mount trolling motor, 4-bank onboard battery charger, Power Pole, 12" manual jack plate, safety and test gear.

YPB#: PB_SKT_ZX250_VF250LA_2014-08-24_BSS

Boat Manufactured By:

Skeeter
One Skeeter Road • Kilgore, TX
(903) 984-0541

www.skeeterboats.com (<http://www.skeeterboats.com>)

