

Boat Manufactured By:



RINKER® CAPTIVA 170 OB

Length	16' 10"
Beam	7' 4"
Dry Weight (Boat Mfr. Pub)	1,400 lbs
Maximum HP	140 hp
Fuel Capacity	22 gal
Weight as Tested	2,414 lbs

F90XA

Horsepower	90 hp
Induction	EFI
Displacement	97 cu. in.
Weight (Estimated)	372 lbs
Gear Ratio	2.27

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Aluminum
Diameter x Pitch	13 x 19
Yamaha Part #	6E5-45941-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	64° F / 43° F
Elevation (in feet above sea level)	840'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 18 gallons of fuel, 1 battery, safety and test gear.

YPB#: PB_RIN_Captiva170OB_F90XA_2015-04-14_RBT



Engine: Yamaha F90XA

Boat: Rinker® Captiva 170 OB

Configuration: Single

Test Date: 14-Apr-2015



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.8	0.4	9.5
1500	5.3	0.7	7.57
2000	6.4	1.1	5.82
2500	7.4	2.1	3.52
3000	9.5	3.2	2.97
3500	19.7	3.4	5.79
4000	24.5	4	6.13
4500	28.7	4.7	6.11
5000	32.7	6	5.45
5500	36.2	7.3	4.96
6000	40.4	9.3	4.34
0-20 MPH: 6.42			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.