

Boat Manufactured By:



6131 Sundance Road • Blackshear, GA  
(912) 449-0033  
[www.sundanceboats.com](http://www.sundanceboats.com)

## SUNDANCE® NX25®

Length	25' 1"
Beam	8' 3"
Dry Weight (Boat Mfr. Pub)	2,735 lbs
Maximum HP	300 hp
Fuel Capacity	72 gal
Weight as Tested	4,260 lbs

## F115TXR / LF115TXR

Horsepower	115 hp
Displacement	106.2 cu. in.
Weight (Estimated)	425 lbs
Gear Ratio	2.15

## ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Anti-Ventilation Plate Height	1/2" Above Boat Bottom

## PROPELLER(S)

Series	Painted Stainless Steel Series
Diameter x Pitch	13 x 19
Yamaha Part #	688-45970-03-98
Propeller Material	Polished Stainless Steel

## TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	82° F / 87° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

## COMMENTS

Test weight includes 1/3 tank of fuel, 2 batteries, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with Yamaha speedometer. Other speed data gathered with GPS receiver.

**YPB#:** PB\_SDC\_NX25\_t\_F115TXR\_2011-07-26\_BAY



**Engine:** Yamaha F115TXR / LF115TXR

**Boat:** Sundance® NX25®

**Configuration:** Twin

**Test Date:** 26-Jul-2011



## PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5	1.3	3.85
1500	6.6	2.1	3.14
2000	8.3	3	2.77
2500	12.7	3.9	3.26
3000	19.4	5.2	3.73
3500	24.8	6.4	3.86
<b>4000</b>	<b>29.8</b>	<b>7.7</b>	<b>3.87</b>
4500	34.8	10.5	3.31
5000	38.3	12.6	3.04
5500	42.2	15.4	2.74
<b>6050</b>	<b>47.1</b>	<b>21.4</b>	<b>2.2</b>
<b>Seconds to Plane: 3.11</b>			
<b>Seconds 0-30 MPH : 5.07</b>			

### NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.