

Boat Manufactured By:



199 Extrusion Place • Hot Springs, AR

(866) 554-5955

www.verandamarine.com

VERANDA VP25RC

Length	27' 8"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,500 lbs
Maximum HP	425 hp
Fuel Capacity	55 gal
Pontoons (#/Diameter)	3 / 27"
Weight as Tested	4,906 lbs

F300XA

Horsepower	300 hp
Induction	EFI
Displacement	4.2L
Weight (Estimated)	551 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CE-45976-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	94° F / 80° F
Elevation (in feet above sea level)	344'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 55 gallons of fuel, 2 batteries, bimini top, safety and test equipment.

YPB#: PB_VER_VP25RC_F300XA_08-18-20_PNT



Engine: Yamaha F300XA

Boat: Veranda VP25RC

Configuration: Single

Test Date: 17-Aug-2020



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.8	1.3	3.81
1500	7.1	1.9	3.72
2000	10.6	3.2	3.34
2500	14.6	4.2	3.46
3000	19.5	6.0	3.27
3500	23.4	7.9	2.97
4000	26.3	10.7	2.46
4500	31.2	13.7	2.27
5000	34.5	17.6	1.95
5500	38.6	23.4	1.65
6000	43.0	25.9	1.66
0-20 MPH: 4.78 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.