

Boat Manufactured By:



2805 Decio Drive • Elkhart, IN 46514
(574) 264-6336

www.benningtonmarine.com

BENNINGTON® 22 SSX

Length	22' 8"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,256 lbs
Maximum HP	150 hp
Fuel Capacity	0 gal
Pontoons (#/Diameter)	2 / Elliptical
Weight as Tested	3,319 lbs

F150LA

Horsepower	150 hp
Induction	EFI
Displacement	2.7 L
Weight (Estimated)	380 lbs
Gear Ratio	2

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series-SD5™
Diameter x Pitch	14 1/2 x 15
Yamaha Part #	68F-45970-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	82° F / 77° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 15 gallons of fuel, 1 battery, optional Twin Elliptical Saltwater Performance Package, safety and test gear.

YPB#: PB_BNT_22SSX_F150LA_2014-10-29_PNT



Engine: Yamaha F150LA

Boat: Bennington® 22 SSX

Configuration: Single

Test Date: 29-Oct-2014



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.6	0.7	6.57
1500	6.7	1.2	5.58
2000	8.3	1.8	4.61
2500	12.2	2.7	4.52
3000	17.5	4	4.38
3500	21.2	5.3	4
4000	26.1	6.6	3.96
4500	30.7	8.3	3.7
5000	35.2	10.3	3.42
5500	39.2	13.1	2.99
6000	42.3	16	2.64
0-20 MPH: 3.3			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.