

Boat Manufactured By:



PO Box 1899 • Cairo, GA
(229) 377-2125

www.southwindboats.com

SOUTHWIND® 212 SD

Length	20' 6"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,500 lbs
Maximum HP	250 hp
Fuel Capacity	50 gal
Weight as Tested	4,148 lbs

F200XB

Horsepower	200 hp
Induction	EFI
Displacement	163 cu. in.
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series-SD5™
Diameter x Pitch	14 1/4 x 17
Yamaha Part #	68F-45972-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	70° F / 65° F
Elevation (in feet above sea level)	194'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes full tank of fuel, 1 battery, safety and test gear.

YPB#: PB_SW_D_212SD_F200XB_2013-01-08_DCK



Engine: Yamaha F200XB

Boat: SouthWind® 212 SD

Configuration: Single

Test Date: 8-Jan-2013



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.1	0.7	5.86
1500	5.9	1.1	5.36
2000	7.5	2	3.75
2500	8.5	3.2	2.66
3000	12.4	4.8	2.58
3500	23.2	5.2	4.46
4000	28	6.4	4.38
4500	32.5	8.2	3.96
5000	37.3	10.8	3.45
5500	42.4	16.1	2.63
6100	47.4	20	2.37
Time to Plane : 4.69			
0-30 MPH: 7.98			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.