

PERFORMANCE BULLETIN

Engine: Yamaha VF250LA


Boat: Skeeter® FXi 21 **Configuration:** Single **Test Date:** 24-Aug-2014



PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	5.6	1.6	3.5
1500	7.3	2.8	2.61
2000	8.1	4.2	1.93
2500	11.1	6.2	1.79
3000	33	7	4.71
3500	38.6	10	3.86
4000	44.5	12.9	3.45
4500	51.1	16.2	3.15
5000	58.4	19.5	3
5500	66.3	21.6	3.07
6100	72.3	23	3.14

0-30 MPH: 6.15



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



SKEETER® FXI 21

Length	21' 0"
Beam	7' 10"
Dry Weight (Boat Mfr. Pub)	2,250 lbs
Maximum HP	250 hp
Fuel Capacity	48 gal
Weight as Tested	3,786 lbs

VF250LA

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
lack Plate	Manual

PROPELLER(S)

Series	VMAX SHO® Ventless Series
Diameter x Pitch	15 1/8 x 25
Yamaha Part #	6CB-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	75° F / 88° F
Elevation (in feet above sea level)	230'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes full tank of fuel, 4 batteries, bow-mount trolling motor, 4-bank onboard battery charger, 12" manual jack plate, safety and test gear.

YPB#: PB_SKT_FXi21_VF250LA_2014-08-24_BSS

Boat Manufactured By:

Skeeter

One Skeeter Road • Kilgore, TX

(903) 984-0541

www.skeeterboats.com (http://www.skeeterboats.com)

