



PERFORMANCE BULLETIN

Engine: Yamaha VF225LA

Boat: Nautic Star® 224 XTS

Configuration: Single


Test Date: 16-Apr-2013



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.7	1.4	3.36
1500	6.7	2.5	2.68
2000	7.8	3.7	2.11
2500	12.4	5.5	2.26
3000	29.3	6.3	4.65
3500	35.2	9.1	3.87
4000	41.2	11.6	3.55
4500	46.6	14.2	3.28
5000	52	16.1	3.23
5500	55.8	18.5	3.02
6050	60.4	21.3	2.84

0-30 MPH: 5.07



NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.



NAUTIC STAR® 224 XTS

Length	22' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,100 lbs
Maximum HP	250 hp
Fuel Capacity	63 gal
Weight as Tested	3,317 lbs

VF225LA

Horsepower	225 hp
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2 on Hydraulic Jack Plate
Ventilation Plate Height	5 1/2" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II™-SDS™
Diameter x Pitch	15 x 21
Yamaha Part #	6CE-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	78° F / 70° F
Elevation (in feet above sea level)	234'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 1 battery, 10" hydraulic jack plate, safety and test gear.

YPB#: PB_NST_224XTS_VF225LA_2013-04-16_BAY

Boat Manufactured By:

Nautic Star
P.O. Box 26 • Amory, MS 38821
(662) 256-5636

www.nauticstarboats.com

(<http://www.nauticstarboats.com>)

