

Boat Manufactured By:

Manitou

7800 Northport Drive • Lansing, MI 48917
(517) 322-3822

www.manitoupontoonboats.com

MANITOU 25 X-PLODE XT SHP

Length	26' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,620 lbs
Maximum HP	350 hp
Fuel Capacity	44 gal
Pontoons (#/Diameter)	3 / SHP
Weight as Tested	5,171 lbs

F350XCC

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	5.3L
Weight (Estimated)	763 lbs
Gear Ratio	1.73:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	16-1/4 x 15
Yamaha Part #	6AW-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 75° F
Elevation (in feet above sea level)	905'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 1 battery, optional sport arch, safety and test equipment.

YPB#: PB_MAN_25XplodeXTSHP_F350XCC_2016-07-13_PNT



Engine: Yamaha F350XCC

Boat: Manitou 25 X-Plode XT SHP

Configuration: Single

Test Date: 12-Jul-2016



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.5	3.33
1500	7.1	2.6	2.73
2000	8.9	4.3	2.07
2500	16.6	5.8	2.86
3000	21.3	7.9	2.70
3500	25.9	10.4	2.49
4000	30.5	13.2	2.31
4500	35.6	16.4	2.17
5000	40.5	18.9	2.14
5500	45.7	25.2	1.81
6100	51.2	31.7	1.62
0-20 MPH: 3.81 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.