

Boat Manufactured By:

## Hurricane

4310 Middlebury St. • Elkhart, IN 46516

(574) 522-8381

www.hurricaneboats.com

### HURRICANE® SUNDECK 2690 OB

Length	26' 4"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	350 hp
Fuel Capacity	98 gal
Weight as Tested	6,061 lbs

### F350XCC

Horsepower	350 hp
Induction	EFI
Displacement	5.3 L
Weight (Estimated)	763 lbs
Gear Ratio	1.73:1

### ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

### PROPELLER(S)

Series	Saltwater Series XL™
Diameter x Pitch	16 1/4 x 15
Yamaha Part #	6AW-45970-20-00
Propeller Material	Polished Stainless Steel

### TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 80° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

### COMMENTS

Test weight includes 50 gallons of fuel, 1 battery, safety and test gear.

**YPB#:** PB\_HUR\_SunDeck2690OB\_F350XCC\_2017-10-11\_DCK



**Engine:** Yamaha F350XCC

**Boat:** Hurricane® SunDeck 2690 OB

**Configuration:** Single

**Test Date:** 11-Oct-2017



### PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.4	1.6	3.38
1500	7.8	2.7	2.89
2000	9.9	4.4	2.25
2500	14.2	6.1	2.33
<b>3000</b>	<b>20.7</b>	<b>8.3</b>	<b>2.49</b>
3500	26.0	10.6	2.45
4000	30.4	14.1	2.16
4500	35.0	17.0	2.06
5000	39.3	20.7	1.90
5500	43.7	27.7	1.58
<b>6000</b>	<b>48.3</b>	<b>33.1</b>	<b>1.46</b>
<b>0-20 MPH: 4.40 seconds</b>			

#### NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.