



## XPRESS® X19 PRO

Length	19' 0"
Beam	7' 11"
Dry Weight (Boat Mfr. Pub)	1,400 lbs
Maximum HP	200 hp
Fuel Capacity	45 gal
Weight as Tested	2,632 lbs

## VF200LA V MAX SHO®

Horsepower	200 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75:1

## ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3 on 10" Manual Jack Plate
Ventilation Plate Height	5 1/4" Above Boat Bottom

## PROPELLER(S)

Series	V MAX SHO®
Diameter x Pitch	15 1/8" x 25
Yamaha Part #	6CB-45972-11-00
Propeller Material	Polished Stainless Steel

## TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 80° F
Elevation (in feet above sea level)	312'
Wind Velocity	0-5 MPH

## COMMENTS

Test weight includes 35 gallons of fuel, 1 battery, bow-mounted trolling motor, onboard battery charger, 10" manual jack plate, safety and test gear.

YPB#: PB\_XPR\_X19Pro\_VF200LA\_2017-08-04\_ALM



**Engine:** Yamaha VF200LA V MAX SHO®

**Boat:** Xpress® X19 Pro

**Configuration:** Single

**Test Date:** 4-Aug-2017



## PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	1.5	3.80
1500	7.6	2.8	2.71
2000	9.6	3.7	2.60
<b>2500</b>	<b>27.2</b>	<b>5.1</b>	<b>5.33</b>
3000	33.7	6.9	4.88
3500	40.1	9.3	4.31
4000	47.2	12.1	3.90
4500	53.6	14.7	3.65
5000	60.8	16.4	3.71
5500	65.8	19.2	3.43
<b>5900</b>	<b>70.0</b>	<b>19.8</b>	<b>3.54</b>

**Time to Plane: 2.99<br /> 0-30 MPH: 4.58**

## NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.