

Boat Manufactured By:



1392 Rimmel Dam Rd. • Malvern, AR 72104
(501) 566-1525

www.verandamarine.com

VERANDA® VP25HTS

Length	25' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	5,000 lbs
Maximum HP	250 hp
Fuel Capacity	40 gal
Pontoon # / Diameter	3 / 27"
Weight as Tested	7,069 lbs

VF250LA V MAX SHO®

Horsepower	250 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	505 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 3/4 x 13
Yamaha Part #	6CE-45930-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 80° F
Elevation (in feet above sea level)	312'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 2 batteries, hard top, safety and test gear.

YPB#: PB_VER_VP25HTS_VF250LA_2017-08-29_PNT



Engine: Yamaha VF250LA V MAX SHO®

Boat: Veranda® VP25HTS

Configuration: Single

Test Date: 29-Aug-2017



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.8	1.4	3.43
1500	6.4	2.1	3.05
2000	7.0	2.9	2.41
2500	8.2	3.8	2.16
3000	9.2	4.9	1.88
3500	13.2	6.8	1.94
4000	18.3	8.9	2.06
4500	25.3	12.4	2.04
5000	31.5	15.1	2.09
5500	35.0	19.5	1.80
6100	39.5	23.0	1.72

0-20: 5.04

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.