

Boat Manufactured By:

GODFREY
 4500 Middlebury Street • Elkhart, Indiana 56516
 (574) 522-8381
www.godfreypontoonboats.com

GODFREY SANPAN 2810 SBW

Length	28' 2"
Beam	10' 0"
Dry Weight (Boat Mfr. Pub)	5,200 lbs
Maximum HP	800 hp
Fuel Capacity	124 gal
Pontoon # / Diameter	3 / 27"
Weight as Tested	7,429 lbs

F300XCA / LF300XCA

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	562 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series 11™
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6CE-45970-20-00 / 6CF-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	51° F / 60° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 75 gallons of fuel, 3 batteries, safety and test gear.

YPB#: PB_GDY_Sanpan_2810_SBW_TW_F300XCA_12-12-18_PNT



Engine: Yamaha F300XCA / LF300XCA

Boat: Godfrey Sanpan 2810 SBW

Configuration: Twin

Test Date: 12-Dec-2018



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	2.5	2.24
1500	8.7	4.2	2.10
2000	16.0	6.5	2.47
2500	21.4	9.4	2.28
3000	26.8	12.5	2.14
3500	32.6	16.3	2.00
4000	38.6	22.1	1.75
4500	43.7	27.8	1.57
5000	48.1	33.8	1.43
5500	53.2	41.4	1.29
6050	58.2	53.6	1.08
0-20 MPH: 3.58 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.