

Boat Manufactured By:



BENNINGTON
2805 Decio Drive • Elkhart, IN 46514
(574) 264-6336
www.benningtonmarine.com

BENNINGTON 27RXSBWAT2

Length	28' 3"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,900 lbs
Maximum HP	700 hp
Fuel Capacity	108 gal
Pontoon # / Diameter	3/ESP
Weight as Tested	7,358 lbs

F350XSA/LF350XSA

Horsepower	350 hp
Induction	EFI
Displacement	4.3L
Weight (Estimated)	629 - 629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Saltwater Series II HP
Diameter x Pitch	15 x 20
Yamaha Part #	6KB-45974-00-00 / 6KA-45974-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	63° F / 67° F
Elevation (in feet above sea level)	860'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 60 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_BNT_27RXSBWAT2_TW_LF350XSA_9-4-2024_PNT



Engine: Yamaha F350XSA/LF350XSA

Boat: Bennington 27RXSBWAT2

Configuration: Twin

Test Date: 4-Sep-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.1	2.5	2.44
1500	8.6	4.5	1.93
2000	16.0	6.4	2.52
2500	22.0	9.3	2.37
3000	27.4	13.4	2.04
3500	33.1	17.8	1.86
4000	38.7	23.4	1.66
4500	45.2	28.9	1.56
5000	50.7	36.3	1.40
5500	56.8	47.7	1.19
6000	62.4	59.8	1.04
0-20 MPH: 3.95			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.