

Boat Manufactured By:

PURSUIT

3901 St. Lucie Boulevard • Ft. Pierce, FL 34946
(772) 465-6006

www.pursuitboats.com

PURSUIT DC 286

Length	30' 0"
Beam	9' 6"
Dry Weight (Boat Mfr. Pub)	9,340 lbs
Maximum HP	600 hp
Fuel Capacity	217 gal
Weight as Tested	11,262 lbs

F300USB2 / LF300USB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	624 - 624 lbs

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II HP
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6KB-45970-00-00 / 6KA-45970-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	79° F / 72° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 200 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_PUR_DC 286_TW_LF300USB2_12-2-2025_ODC



Engine: Yamaha F300USB2 / LF300USB2

Boat: Pursuit DC 286

Configuration: Twin

Test Date: 2-Dec-2025



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.6	1.5	3.73
1500	7.9	4.3	1.84
2000	9.6	7.5	1.28
2500	12.8	10.9	1.17
3000	19.7	13.4	1.47
3500	30.3	16.5	1.84
4000	36.5	23.0	1.59
4500	41.8	29.1	1.44
5000	46.9	37.4	1.25
5500	51.7	48.1	1.07
6000	55.0	52.8	1.04
0-30 MPH: 7.80 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.