

Boat Manufactured By:



WORLD CAT 260 DC

Length	25' 6"
Beam	9' 0"
Dry Weight (Boat Mfr. Pub)	6,150 lbs
Maximum HP	400 hp
Fuel Capacity	180 gal
Weight as Tested	8,370 lbs

LF200XSA2 / F200XSA2

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	525 - 525 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	2 1/2" Above Boat Bottom

PROPELLER(S)

Series	Reliance
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68G-45978-20-00 / 68F-45978-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	90° F / 85° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 90 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_WCC_260 DC_TW_LF200XSA2_08-29-2023_CAT



Engine: Yamaha LF200XSA2 / F200XSA2

Boat: World Cat 260 DC

Configuration: Twin

Test Date: 29-Aug-2023



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	1.9	3.08
1500	7.4	2.9	2.53
2000	8.7	5.0	1.76
2500	13.1	7.2	1.81
3000	19.7	9.4	2.09
3500	26.2	11.9	2.21
4000	31.6	15.6	2.03
4500	36.6	20.5	1.78
5000	41.3	27.4	1.51
5500	46.6	35.9	1.30
5800	49.7	40.1	1.24

0-20 MPH: 5.75 seconds / **0-30 MPH: 9.05 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.