

Boat Manufactured By:

# ALUMA Craft

315 West St. Julien Street • St. Peter, MN 56082

(507) 931-1050

[www.alumacraft.com](http://www.alumacraft.com)

## ALUMACRAFT ESCAPE 165 TILLER

Length	16' 6"
Beam	6' 4"
Dry Weight (Boat Mfr. Pub)	646 lbs
Maximum HP	50 hp
Weight as Tested	1,489 lbs

## F50LB

Horsepower	50 hp
Induction	EFI
Displacement	60.8 cc
Weight (Estimated)	247 lbs
Gear Ratio	1.85:1

## ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Below Boat Bottom

## PROPELLER(S)

Series	Aluminum Series
Diameter x Pitch	10-5/8 x 12
Yamaha Part #	6H5-45952-00-00
Propeller Material	Aluminum

## TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	37° F / 48° F
Elevation (in feet above sea level)	975'
Wind Velocity	10-15 MPH

## COMMENTS

Test weight includes 4 gallons of fuel, 2 batteries, bow-mounted trolling motor, safety and test equipment.

**YPB#:** PB\_ALM\_Escape165Tiller\_F50LB\_2013-10-21\_ALM



**Engine:** Yamaha F50LB

**Boat:** Alumacraft Escape 165 Tiller

**Configuration:** Single

**Test Date:** 20-Oct-2013



## PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.3	0.3	11.00
1500	4.5	0.5	9.00
2000	5.9	1.0	5.90
2500	6.7	1.2	5.58
3000	8.8	1.7	5.18
3500	14.8	1.9	7.79
4000	20.0	2.3	8.70
<b>4500</b>	<b>23.6</b>	<b>2.7</b>	<b>8.74</b>
5000	26.6	3.2	8.31
5500	29.8	4.1	7.27
<b>5950</b>	<b>33.1</b>	<b>5.0</b>	<b>6.62</b>
<b>0-20 MPH: 5.86 seconds</b>			

## NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.