

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946

{0:(772) 465-0631}

www.cobiaboats.com

- Cobia® 280 DC

COBIA® 280 DC

Length	27' 7"
Beam	9' 8"
Dry Weight (Boat Mfr. Pub)	5,680 lbs
Maximum HP	500 hp
Fuel Capacity	172 gal
Weight as Tested	7,682 lbs

F200XCA / LF200XCA

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/4
Yamaha Part #	68F-45972-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	84° F / 75° F
Elevation (in feet above sea level)	0"
Elevation (in feet above sea level)	5-10 MPH

COMMENTS

Test weight includes 120 gallons of fuel, 4 batteries, 25 gallons saltwater, safety and test gear.

YPB#: PB_COB_280DC_t_F200XCA_2017-06-09_ODC

Engine: Yamaha F200XCA / LF200XCA

F200XCA / LF200XCA

Boat: Cobia® 280 DC

Configuration: Twin

Test Date: 9-Jun-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.3	1.6	3.31
1500	7.4	2.6	2.85
2000	8.6	4.4	1.96
2500	10.6	6.5	1.63
3000	16	8.9	1.8
3500	21.7	12.1	1.79
4000	29.3	13.7	2.14
4500	35.3	19.5	1.81
5000	40.5	25.5	1.59
5500	44	35.1	1.25
6000	47.8	39.6	1.21
0-30 MPH: 8.61			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.