PERFORMANCE BULLETIN

Boat Manufactured By:

VERANDA

1392 Remmel Dam Rd. • Malvern, AR 72104
(501) 566-1525
www.verandamarine.com



VR265VLIT

Length	26' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,400 lbs
Maximum HP	300 hp
Fuel Capacity	50 gal
Pontoon # / Diameter	3 x 27
Weight as Tested	4,697 lbs

VF250LB

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	567 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CE-45976-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 84° F
Elevation (in feet above sea level)	299'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 45 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_VER_VR265VLIT_VF250LB_09-02-25_PNT

Engine: *Yamaha VF250LB*

Boat: *VR265VLIT*

Configuration: *Single*

Test Date: *2-Sep-2025*



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.4	3.65
1500	7.1	2.1	3.38
2000	8.2	2.6	3.10
2500	**10.0**	**3.4**	**2.90**
3000	12.9	4.8	2.66
3500	18.4	7.4	2.49
4000	23.1	9.7	2.39
4500	28.3	13.7	2.06
5000	35.7	16.4	2.18
5500	40.1	21.4	1.87
5900	**44.0**	**23.0**	**1.92**

0-20 MPH: 3.77 seconds

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.