

Boat Manufactured By:



650 River Ave • South Gardiner , ME 4359
(207) 620-7998

www.southportboats.com

SOUTHPORT 33 DC

Length	33' 0"
Beam	10' 7"
Dry Weight (Boat Mfr. Pub)	9,800 lbs
Maximum HP	900 hp
Fuel Capacity	250 gal
Weight as Tested	12,798 lbs

LF350XSA2 / F350XSA2

Horsepower	350 hp
Induction	EFI/VC/DOHC
Displacement	4.3L
Weight (Estimated)	629 - 629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6CF-45970-20-00 / 6CE-45970-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	76° F / 72° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 125 gallons of fuel, 8 batteries, safety and test equipment.

YPB#: PB_SOU_33 DC_TW_LF350XSA2_3-26-24_ODC



Engine: Yamaha LF350XSA2 / F350XSA2

Boat: Southport 33 DC

Configuration: Twin

Test Date: 26-Mar-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.4	2.5	2.56
1500	8.4	4.5	1.88
2000	10.0	7.0	1.44
2500	13.8	11.2	1.23
3000	17.7	14.8	1.20
3500	26.3	17.4	1.51
4000	33.2	23.7	1.40
4500	38.4	29.6	1.30
5000	42.9	39.4	1.09
5500	48.4	53.9	0.90
6000	52.2	61.9	0.84
0-20 MPH: 5.65 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.