

Boat Manufactured By:

Manitou

16020 South Lowell Road • Lansing, MI 48906
(517) 322-3822

www.manitoupontoonboats.com

MANITOU 25 LX SRW

Length	26' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,900 lbs
Maximum HP	425 hp
Fuel Capacity	45 gal
Pontoon # / Diameter	3 / SHP575 Gen II
Weight as Tested	5,229 lbs

F350XSA

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	68° F / 59° F
Elevation (in feet above sea level)	929'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 2 batteries, Sport Tower, safety and test equipment.

YPB#: PB_MAN_25 LX SRW_F350XSA_9-29-26_PNT



Engine: Yamaha F350XSA

Boat: Manitou 25 LX SRW

Configuration: Single

Test Date: 29-Sep-2026



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.1	1.2	4.43
1500	7.0	2.0	3.59
2000	9.1	3.1	2.97
2500	15.1	4.8	3.14
3000	19.2	6.4	3.02
3500	22.5	8.1	2.77
4000	25.8	11.3	2.28
4500	33.1	14.9	2.22
5000	40.0	19.4	2.06
5500	46.4	23.9	1.94
6050	52.3	29.6	1.77
0-20 MPH: 4.61 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.