

Boat Manufactured By:

SEA PRO

25214 Hwy 121 • Whitmire, SC 29178
 (803) 694-2644
 seapromfg.com

SEA PRO CITATION 2400

Length	23' 8"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,200 lbs
Maximum HP	300 hp
Fuel Capacity	70 gal
Weight as Tested	5,716 lbs

F300XCB

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	556 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Boat Bottom

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 84° F
Elevation (in feet above sea level)	250'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 70 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_SPR_Citation 2400_F300XCB_8-23-2022_DCK



Engine: Yamaha F300XCB

Boat: Sea Pro Citation 2400

Configuration: Single

Test Date: 23-Aug-2022



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.1	1.3	4.69
1500	7.8	2.2	3.55
2000	9.6	3.7	2.59
2500	14.8	5.3	2.79
3000	24.9	6.3	3.95
3500	30.9	8.2	3.77
4000	35.3	11.3	3.12
4500	40.1	14.8	2.71
5000	44.6	17.7	2.52
5500	49.1	22.8	2.15
5900	51.8	26.1	1.98

Time to Plane: 3.15 seconds / **0-30 MPH: 5.69 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.