

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946
(772) 465-0631

www.pathfinderboats.com

PATHFINDER 2800 HYBRID

Length	28' 5"
Beam	9' 5"
Dry Weight (Boat Mfr. Pub)	5,928 lbs
Maximum HP	700 hp
Fuel Capacity	182 gal
Weight as Tested	8,380 lbs

F300XSB2 / LF300XSB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	611 - 611 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II HP
Diameter x Pitch	15 x 21
Yamaha Part #	6KB-45976-00-00 / 6KA-45976-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 76° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 170 gallons of fuel, 3 batteries, Trolling Motor, Dual Power Poles, Stand Through second station, safety and test equipment.

YPB#: PB_PAT_2800 Hybrid_TW_LF300XSB2_4-15-26_BAY



Engine: Yamaha F300XSB2 / LF300XSB2

Boat: Pathfinder 2800 Hybrid

Configuration: Twin

Test Date: 15-Apr-2026



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.9	2.6	2.27
1500	8.1	4.5	1.79
2000	9.2	8.5	1.08
2500	15.1	12.9	1.18
3000	28.6	14.0	2.05
3500	36.7	17.8	2.06
4000	43.1	23.9	1.80
4500	48.9	30.2	1.62
5000	54.8	38.8	1.41
5500	59.3	46.5	1.27
6100	63.9	53.1	1.20
0-20 MPH: 5.96 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.