

Boat Manufactured By:

PURSUIT

3901 St. Lucie Boulevard • Ft. Pierce, FL 34946
(772) 465-6006

www.pursuitboats.com

PURSUIT DC 266

Length	27' 4"
Beam	8' 9"
Dry Weight (Boat Mfr. Pub)	6,800 lbs
Maximum HP	400 hp
Fuel Capacity	139 gal
Weight as Tested	8,802 lbs

F150XCA / LF150XCA

Horsepower	150 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	487 lbs
Gear Ratio	2.00:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/4 x 17
Yamaha Part #	68F-45972-20-00 / 68G-45972-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	76° F / 74° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Tested weight includes 139 Gallons of fuel, 20 Gallons of water, 3 people, safety and test gear

YPB#: PB_PUR_DC266_TW_F150XCA_03-25-2019_OCC



Engine: Yamaha F150XCA / LF150XCA

Boat: Pursuit DC 266

Configuration: Twin

Test Date: 24-Mar-2019



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.0	1.7	3.03
1500	7.1	2.7	2.63
2000	8.6	4.2	2.07
2500	9.6	6.1	1.57
3000	15.0	7.8	1.92
3500	21.8	10.3	2.12
4000	27.7	12.8	2.17
4500	32.5	16.3	2.00
5000	37.1	20.6	1.81
5500	41.1	25.7	1.60
6000	45.1	31.3	1.44
0-30 MPH: 8.04 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.