

Boat Manufactured By:



901 Cowan Drive • Lebanon, MO 65536
(417) 588-9787
www.g3boats.com

G3 SELECT 320 RCX

Length	20' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,343 lbs
Maximum HP	115 hp
Fuel Capacity	46 gal
Pontoon # / Diameter	3/23"x25"
Weight as Tested	3,425 lbs

VF115XA

Horsepower	115 hp
Induction	EFI/VCT/DOHC
Displacement	1.8L
Weight (Estimated)	386 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Talon Pontoon
Diameter x Pitch	14 x 13
Yamaha Part #	6H1-45978-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	92° F / 87° F
Elevation (in feet above sea level)	867'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 46 gallons of fuel, 1 battery, 2 people, bimini top up and stowed, safety and test equipment.

YPB#: PB_G3B_Select 320RCX_VF115XA_06-18-24_PNT



Engine: Yamaha VF115XA

Boat: G3 Select 320 RCX

Configuration: Single

Test Date: 18-Jun-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.5	0.6	6.23
1500	5.2	0.9	5.80
2000	6.6	1.2	5.31
2500	8.0	2.1	3.87
3000	11.7	2.7	4.41
3500	16.5	3.4	4.91
4000	20.5	4.4	4.64
4500	24.7	5.3	4.63
5000	28.6	7.3	3.89
5500	32.6	9.1	3.57
6000	35.6	11.7	3.05
6200	36.7	11.8	3.12
0-20 MPH: 5.81 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.