

Boat Manufactured By:



Wellcraft®

925 Frisbie Street • Cadillac, MI

(231) 775-1351

www.wellcraft.com

WELLCRAFT® 302 FISHERMAN

Length	30' 2"
Beam	9' 8"
Dry Weight (Boat Mfr. Pub)	6,700 lbs
Maximum HP	800 hp
Fuel Capacity	268 gal
Weight as Tested	9,295 lbs

F300XCA / LF300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Ventilation Plate Height	Even With Boat Bottom

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	54° F / 45° F
Elevation (in feet above sea level)	1305'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 134 gallons of fuel, 3 batteries, safety and test gear.

YPB#: PB_WLC_302Fisherman_t_F300XCA_2017-04-19_OCC



Engine: Yamaha F300XCA / LF300XCA

Boat: Wellcraft® 302 Fisherman

Configuration: Twin

Test Date: 19-Apr-2017

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.2	2.5	2.48
1500	8.2	4.1	2
2000	9.3	7.1	1.31
2500	10.6	10.8	0.98
3000	15.3	14.5	1.06
3500	29.2	17.3	1.69
4000	35	22.1	1.58
4500	39.8	28.5	1.4
5000	44.8	34.9	1.28
5500	49.3	41.1	1.2
5900	52.4	50.7	1.03
0-20 MPH: 4.84
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.