

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946
(772) 465-0631

www.pathfinderboats.com

PATHFINDER 2800 HYBRID

Length	28' 0"
Beam	9' 4"
Dry Weight (Boat Mfr. Pub)	7,930 lbs
Maximum HP	700 hp
Fuel Capacity	182 gal
Weight as Tested	10,370 lbs

F350XSA / LF350XSA

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 - 629 lbs

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	14-3/4 x 25
Yamaha Part #	6CF-45D74-20-00 / 6CE-45D74-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	80° F / 64° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 115 gallons of fuel, 6 batteries, Trolling Motor, Dual Power Poles, 2nd Station, safety and test equipment.

YPB#: PB_PAT_2800 Hybrid_TW_LF350XSA_1-27-26_BAY



Engine: Yamaha F350XSA / LF350XSA

Boat: Pathfinder 2800 Hybrid

Configuration: Twin

Test Date: 27-Jan-2026



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	6.6	2.6	2.57
1500	8.5	4.7	1.83
2000	9.8	8.6	1.14
2500	17.0	14.0	1.21
3000	32.0	15.6	2.05
3500	40.0	19.4	2.07
4000	46.5	25.1	1.85
4500	53.5	32.2	1.66
5000	58.4	39.5	1.48
5500	64.5	53.2	1.21
6100	69.4	60.8	1.14
0-20 MPH: 11.11 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.