

Boat Manufactured By:



JEANNEAU
 105 Eastern Avenue #202 • Annapolis, MD 21403
 (410) 280-9400
www.jeanneau.com

JEANNEAU NC 1095

Length	34' 5"
Beam	10' 11"
Dry Weight (Boat Mfr. Pub)	10,225 lbs
Maximum HP	600 hp
Fuel Capacity	212 gal
Weight as Tested	13,125 lbs

F300UCA / LF300UCA

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	575 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CE-45976-20-00 / 6CF-45976-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	73° F / 69° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 150 gallons of fuel, 3 batteries, safety and test gear.

YPB#: PB_JEA_NC 1095_T_F300UCA_7-24-18_OWA



Engine: Yamaha F300UCA / LF300UCA

Boat: Jeanneau NC 1095

Configuration: Twin

Test Date: 23-Jul-2018



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	2.5	2.28
1500	7.5	4.1	1.83
2000	9.7	6.8	1.42
2500	10.7	10.2	1.04
3000	12.9	13.1	0.98
3500	17.5	16.9	1.04
4000	27.7	23.4	1.19
4500	32.9	30.2	1.09
5000	37.0	36.4	1.02
5500	40.5	46.1	0.88
6000	44.2	52.4	0.84
0-20 MPH: 5.60 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.