

Boat Manufactured By:



- Bennington® 2275 GCW

BENNINGTON® 2275 GCW

Length	24' 9"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,525 lbs
Maximum HP	200 hp
Fuel Capacity	0 gal
Pontoons Diameter	CMS.Helpers.HTMLHelper.StripTags(Html.Raw(Model.BoatPontoonDiameter)).ToString()
Weight as Tested	3,626 lbs

Engine: Yamaha F200LA

F200LA

Boat: Bennington® 2275 GCW

Configuration: Single

Test Date: 29-Oct-2014

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.4	0.8	5.5
1500	6.4	1.3	4.92
2000	8.4	2.1	4
2500	13.5	3.1	4.36
3000	17.9	4	4.48
3500	23.6	5.9	4
4000	28.5	7.7	3.7
4500	33	10	3.3
5000	37.6	13.9	2.71
5500	41.4	17.1	2.42
5900	44.7	19.5	2.29
0-20 MPH: 3.66			

F200LA

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	487 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance® Series-SDS™
Diameter x Pitch	14 1/2
Yamaha Part #	68F-45970-10-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 78° F
Elevation (in feet above sea level)	0"
Elevation (in feet above sea level)	0-5 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 1 battery, optional Twin Elliptical Saltwater Performance Package, safety and test gear.

YPB#: PB_BNT_2275GCW_F200LA_2014-10-29_PNT

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.