PERFORMANCE BULLETIN

Boat Manufactured By:

GODFREY

4500 Middlebury Street • Elkhart, Indiana 56516

(574) 522-8381

www.godfreypontoonboats.com

GODFREY SWEETWATER 2286 CPSE

Length	23' 10"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,000 lbs
Maximum HP	300 hp
Fuel Capacity	45 gal
Pontoon # / Diameter	3 / Impact
Weight as Tested	4,375 lbs

F150XD

Horsepower	150 hp
Induction	EFI/VCT/DOHC
Displacement	2.7L
Weight (Estimated)	525 lbs
Gear Ratio	2:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2

PROPELLER(S)

Series	Reliance
Diameter x Pitch	14-1/2 x 15
Yamaha Part #	68F-45970-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	79° F / 74° F
Elevation (in feet above sea level)	859'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 40 gallons of fuel, 1 battery, safety and test equipment.

YPB#: PB_GOD_Sweetwater 2286 CPSE_F150XD_8-10-26_PNT

Engine: *Yamaha F150XD*

Boat: *Godfrey Sweetwater 2286 CPSE*

Configuration: *Single*

Test Date: *10-Aug-2026*

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.1	0.8	5.13
1500	5.8	1.3	4.42
2000	7.4	1.9	3.87
2500	9.8	2.8	3.56
3000	**15.3**	**3.9**	**3.97**
3500	19.5	5.3	3.68
4000	24.0	6.8	3.55
4500	27.5	8.8	3.14
5000	32.1	10.8	2.97
5500	36.3	13.6	2.68
5900	**40.0**	**16.0**	**2.50**

0-20 MPH: 5.90 seconds

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.