

Boat Manufactured By:

 625 Railroad Avenue • Hartsville, SC
 (843) 383-4507
 www.stingrayboats.com

259 DC

Length	25' 3"
Beam	9' 3"
Dry Weight (Boat Mfr. Pub)	4,542 lbs
Maximum HP	450 hp
Fuel Capacity	120 gal
Weight as Tested	6,366 lbs

LF150XSA / F150XSA2

Horsepower	150 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	522 - 522 lbs
Gear Ratio	2:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1" Above Boat Bottom

PROPELLER(S)

Series	Reliance® Series
Diameter x Pitch	14-1/4 x 18
Yamaha Part #	68G-45978-20-00 / 68F-45978-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	62° F / 75° F
Elevation (in feet above sea level)	200'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_STG_259 DC_TW_LF150XSA_11-3-2025_ODC



Engine: Yamaha LF150XSA / F150XSA2

Boat: 259 DC

Configuration: Twin

Test Date: 3-Nov-2025



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.3	1.6	3.28
1500	7.1	2.7	2.61
2000	8.6	4.2	2.05
2500	11.7	6.0	1.97
3000	17.8	7.5	2.37
3500	24.9	9.5	2.62
4000	30.3	12.0	2.52
4500	35.0	15.4	2.28
5000	39.4	20.2	1.95
5500	43.5	25.4	1.71
6100	48.0	32.3	1.48

Time to Plane: 3.51 seconds / **0-30 MPH: 5.65 seconds**

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.