

Boat Manufactured By:



1392 Rimmel Dam Rd. • Malvern, AR 72104

(501) 566-1525

www.verandamarine.com

VERANDA V ONE

Length	25' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,400 lbs
Maximum HP	600 hp
Fuel Capacity	100 gal
Pontoon # / Diameter	3 / 27"
Weight as Tested	6,860 lbs

F300XSB2 / LF300XSB2

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	611 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6CE-45970-20-00 / 6CF-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	3
Air / Water Temperature (Fahrenheit)	62° F / 47° F
Elevation (in feet above sea level)	338'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 80 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_VER_V One_F300XSB_02-08-22_PNT



Engine: Yamaha F300XSB2 / LF300XSB2

Boat: Veranda V One

Configuration: Twin

Test Date: 8-Feb-2022



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.7	2.7	2.13
1500	8.2	4.5	1.84
2000	13.8	7.2	1.92
2500	20.2	9.2	2.19
3000	26.4	12.1	2.19
3500	32.2	15.6	2.06
4000	37.4	21.6	1.73
4500	42.6	27.7	1.54
5000	47.6	35.5	1.34
5500	51.9	43.7	1.19
6000	56.7	53.1	1.07
0-20 MPH: 3.00 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.