

Boat Manufactured By:



WORLD CAT 230SD

Length	22' 7"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,428 lbs
Maximum HP	230 hp
Fuel Capacity	89 gal
Weight as Tested	5,501 lbs

F115XB / LF115XB

Horsepower	115 hp
Induction	EFI/DOHC
Displacement	1.8L
Weight (Estimated)	386 - 386 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
------------------------	----

PROPELLER(S)

Series	Talon SS
Diameter x Pitch	13-1/8 x 16
Yamaha Part #	6N7-45972-00-00 / 6N4-45972-00-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 84° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes half tank fuel, 2 batteries, 2 people and 30 lbs of safety gear on board.

YPB#: PB_WCC_230SD_T_F115_8-21-18_revised_CAT



Engine: Yamaha F115XB / LF115XB

Boat: World Cat 230SD

Configuration: Twin

Test Date: 20-Aug-2018

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.5	0.9	5.00
1500	6.2	1.8	3.54
2000	7.5	2.7	2.78
2500	9.1	4.2	2.18
3000	13.5	5.6	2.43
3500	19.7	7.1	2.77
4000	25.4	8.7	2.91
4500	29.7	11.0	2.70
5000	33.3	14.0	2.38
5500	36.8	18.0	2.05
5950	40.3	21.1	1.91
0-20 MPH: 4.63 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.