

Boat Manufactured By:
ALUMACraft
 315 West St. Julien Street • St. Peter, MN 56082
 (507) 931-1050
www.alumacraft.com

ALUMACRAFT TROPHY 190X SPORT

Length	20' 2"
Beam	8' 2"
Dry Weight (Boat Mfr. Pub)	1,929 lbs
Maximum HP	200 hp
Fuel Capacity	36 gal
Weight as Tested	3,076 lbs

VF200XB

Horsepower	200 hp
Induction	EFI/VC/D/DOHC
Displacement	4.2L
Weight (Estimated)	567 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-3/4 x 15
Yamaha Part #	6CE-45976-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	74° F / 66° F
Elevation (in feet above sea level)	1253'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 30 gallons of fuel, 5 batteries, bow mount trolling motor, safety and test equipment.

YPB#: PB_ALM_Trophy 190X Sport_VF200XB_8/31/26_ALM



Engine: Yamaha VF200XB

Boat: Alumacraft Trophy 190X Sport

Configuration: Single

Test Date: 31-Aug-2026



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.3	4.40
1500	7.0	2.2	3.26
2000	8.2	3.2	2.55
2500	12.9	4.4	2.93
3000	22.6	5.5	4.14
3500	28.6	7.5	3.81
4000	32.1	9.8	3.29
4500	35.2	12.7	2.77
5000	39.4	14.0	2.82
5500	43.4	17.2	2.53
5950	46.2	18.8	2.46
0-20 MPH: 3.81 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.