

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946
(772) 465-0631

www.pathfinderboats.com

PATHFINDER 2200 TRS

Length	22' 1"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,143 lbs
Maximum HP	250 hp
Fuel Capacity	65 gal
Weight as Tested	4,401 lbs

VF200XB

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	567 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	On Hydraulic Jack Plate

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/2 x 17
Yamaha Part #	6CE-45978-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 82° F
Elevation (in feet above sea level)	0'
Wind Velocity	10-15 MPH

COMMENTS

Tested weight includes 2 people, 3 batteries, Hydraulic Jackplate, Hardtop, trolling motor, and 2 power poles.

YPB#: PB_PAT_2200 TRS_VF200XB_05-15-23_BAY



Engine: Yamaha VF200XB

Boat: Pathfinder 2200 TRS

Configuration: Single

Test Date: 15-May-2023



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.1	1.4	3.61
1500	7.8	2.3	3.44
2000	9.4	3.5	2.69
2500	14.8	4.8	3.07
3000	24.3	6.3	3.89
3500	29.3	8.4	3.49
4000	34.5	11.3	3.07
4500	39.6	14.1	2.81
5000	43.9	16.3	2.70
5500	48.8	19.5	2.51
5800	50.8	19.7	2.59
0-20 MPH: 3.88 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.