PERFORMANCE BULLETIN

Boat Manufactured By:

Manitou

7800 Northport Drive • Lansing, MI 48917
(517) 322-3822
www.manitoupontoonboats.com

MANITOU 26 EXPLORE SHP575

Length	27' 3"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,239 lbs
Maximum HP	400 hp
Fuel Capacity	43 gal
Pontoon # / Diameter	3 / SHP
Weight as Tested	5,837 lbs

F300XCB

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	556 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#1

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/2 x 16
Yamaha Part #	6CE-45938-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	3
Elevation (in feet above sea level)	938'
Wind Velocity	10-15 MPH

COMMENTS

Test weight includes 42 gallons of fuel, 2 batteries, safety and test equipment.

YPB#: PB_MAN_26 Explore SHP575_F300XCB_10-23-24_PNT

Engine: *Yamaha F300XCB*

Boat: *Manitou 26 Explore SHP575*

Configuration: *Single*

Test Date: *23-Oct-2024*

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	4.9	1.9	2.62
1500	6.8	1.9	3.58
2000	9.7	3.3	2.97
2500	**15.4**	**4.4**	**3.49**
3000	19.4	5.8	3.34
3500	23.6	7.6	3.12
4000	27.7	10.4	2.68
4500	31.8	13.3	2.39
5000	36.3	16.3	2.23
5500	40.8	19.2	2.13
6050	**45.8**	**26.1**	**1.76**

0-20 MPH: 3.68 seconds

NOTICE TO CONSUMER
The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.