

Boat Manufactured By:



901 Cowan Drive • Lebanon, MO 65536
 (417) 588-9787
 www.g3boats.com

- G3 Boats® Angler V16 F

G3 BOATS® ANGLER V16 F

Length	16' 4"
Beam	7' 4"
Dry Weight (Boat Mfr. Pub)	1,080 lbs
Maximum HP	90 hp
Fuel Capacity	19 gal
Weight as Tested	1,937 lbs

F70LA

Horsepower	70 hp
Induction	EFI
Displacement	60.8 cu. in.
Weight (Estimated)	253 lbs
Gear Ratio	2.33

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Aluminum
Diameter x Pitch	13 1/2
Yamaha Part #	6E5-45947-00-00
Propeller Material	Aluminum

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	70° F / 81° F
Elevation (in feet above sea level)	906"
Elevation (in feet above sea level)	0-5 MPH

COMMENTS

Test weight includes 11 gallons of fuel, 2 batteries, bow-mounted trolling motor, safety and test gear.

YPB#: PB_G3B_AnglerV16F_F70LA_2016-07-15_ALM

Engine: Yamaha F70LA

F70LA

Boat: G3 Boats® Angler V16 F

Configuration: Single

Test Date: 15-Jul-2016

PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.6	0.3	12
1500	5.2	0.5	10.4
2000	6.3	1	6.3
2500	7.6	1.5	5.07
3000	11.1	1.8	6.17
3500	17.2	2.2	7.82
4000	21.1	2.6	8.12
4500	25.1	3.2	7.84
5000	28.1	4	7.03
5500	30.9	5	6.18
6000	33.9	5.9	5.75
0-20 MPH: 5.82			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.