PERFORMANCE BULLETIN

Boat Manufactured By:

16 Industry Parkway NW • Melrose, MN
(320) 256-2628
www.warriorboatsinc.com



V1890 BACKTROLLER

Length	18' 3"
Beam	7' 6"
Dry Weight (Boat Mfr. Pub)	1,700 lbs
Maximum HP	90 hp
Fuel Capacity	33 gal
Weight as Tested	2,670 lbs

VF90XA

Horsepower	90 hp
Induction	EFI/VCT/DOHC
Displacement	1.8L
Weight (Estimated)	362 lbs
Gear Ratio	2.15:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2

PROPELLER(S)

Series	Talon GP™
Diameter x Pitch	13-1/8 x 17
Yamaha Part #	6FP-45947-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	65° F / 68° F
Elevation (in feet above sea level)	1380'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 18 gallons of fuel, 1 battery, Minn Kota Vantage, safety and test equipment.

YPB#: PB_WAR_V1890 Backtroller_0_VF90XA_9-24-25_WLY

Engine: *Yamaha VF90XA*

Boat: *V1890 Backtroller*

Configuration: *Single*

Test Date: *24-Sep-2025*



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	3.4	0.5	6.70
1500	5.0	0.8	6.19
2000	6.3	1.1	5.68
2500	7.1	1.8	3.92
3000	8.2	2.9	2.86
3500	10.5	3.9	2.68
4000	**24.3**	**3.6**	**6.85**
4500	28.3	4.4	6.49
5000	32.5	5.2	6.24
5500	36.3	6.6	5.54
6100	**40.1**	**10.0**	**4.03**

0-20 MPH: 5.82 seconds

NOTICE TO CONSUMER
The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.