

Boat Manufactured By:

Hurricane

4310 Middlebury St. • Elkhart, IN 46516
(574) 522-8381

www.hurricaneboats.com

HURRICANE SD 2600

Length	26' 5"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	4,370 lbs
Maximum HP	400 hp
Fuel Capacity	66 gal
Weight as Tested	6,029 lbs

F350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 18
Yamaha Part #	6CE-45934-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	73° F / 72° F
Elevation (in feet above sea level)	860'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 2 batteries, windless anchor, safety and test equipment.

YPB#: PB_HUR_SD 2600_F350XSA2_8-11-24_DCK



Engine: Yamaha F350XSA2

Boat: Hurricane SD 2600

Configuration: Single

Test Date: 11-Aug-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.2	4.54
1500	7.2	2.1	3.51
2000	8.7	3.4	2.56
2500	14.2	5.0	2.86
3000	22.1	6.5	3.42
3500	29.3	8.2	3.60
4000	34.8	11.0	3.17
4500	38.7	13.7	2.84
5000	42.8	17.8	2.41
5500	47.8	22.5	2.12
6000	53.1	30.2	1.76
0-20 MPH: 5.23 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.