

Boat Manufactured By:



3207 Industrial 29th Street • Ft. Pierce, FL 34946

(772) 465-0631

www.pathfinderboats.com

2600 TRS

Length	26' 2"
Beam	8' 10"
Maximum HP	450 hp
Fuel Capacity	88 gal
Weight as Tested	1,441 lbs

F350XSA2

Horsepower	350 hp
Induction	EFI/VCT/DOHC
Displacement	4.3L
Weight (Estimated)	629 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6KA-45972-00-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	83° F / 80° F
Elevation (in feet above sea level)	0'
Wind Velocity	15-20 MPH

COMMENTS

Test weight includes 77 gallons of fuel, 5 batteries, Second station, Dual Power poles, Trolling motor, SeaKeeper Ride, safety and test equipment.

YPB#: PB_PAT_2600 TRS_0_F350XSA2_10-16-2025_BAY



Engine: Yamaha F350XSA2

Boat: 2600 TRS

Configuration: Single

Test Date: 16-Oct-2025



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.4	1.2	4.50
1500	7.3	2.2	3.40
2000	8.7	4.0	2.18
2500	11.8	6.4	1.86
3000	19.6	8.2	2.40
3500	30.5	10.0	3.06
4000	35.8	12.5	2.86
4500	41.5	15.4	2.70
5000	46.9	20.2	2.32
5500	52.1	28.1	1.85
6000	55.1	30.2	1.83
0-20 MPH: 7.24 Seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.