

Boat Manufactured By:



901 Cowan Drive • Lebanon, MO 65536
 (417) 588-9787
 www.g3boats.com

G3 BOATS® ANGLER V19 F

Length	19' 2"
Beam	8' 0"
Dry Weight (Boat Mfr. Pub)	1,780 lbs
Maximum HP	200 hp
Fuel Capacity	40 gal
Weight as Tested	2,998 lbs

VF175XA V MAX SHO

Horsepower	175 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
------------------------	----

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/4 x 17
Yamaha Part #	68F-45972-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	87° F / 85° F
Elevation (in feet above sea level)	918'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 20 gallons of fuel, 3 batteries, bow-mounted trolling motor, safety and test gear.

YPB#: PB_G3B_AnglerV19F_VF175XA_2017-07-09_ALM



Engine: Yamaha VF175XA V MAX SHO

Boat: G3 Boats® Angler V19 F

Configuration: Single

Test Date: 9-Jul-2017



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5	0.9	5.56
1500	6.6	1.3	5.08
2000	7.9	2.1	3.76
2500	13.7	2.7	5.07
3000	22.7	3.3	6.88
3500	27.4	4.3	6.37
4000	31.7	6.2	5.11
4500	35.9	7.6	4.72
5000	40.1	9.9	4.05
5500	44.4	13.3	3.34
6100	50	18.2	2.75
0-30 MPH: 4.83
			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.