

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

(903) 984-0541

www.skeeterboats.com

SKEETER SX2550

Length	24' 6"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	3,660 lbs
Maximum HP	300 hp
Fuel Capacity	76 gal
Weight as Tested	5,606 lbs

F300XCB

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	556 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/4 x 19
Yamaha Part #	6CE-45970-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	85° F / 90° F
Elevation (in feet above sea level)	375'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 70 gallons of fuel, 4 batteries, 2 people, 12" Hydraulic jackplate, 36 volt trolling motor, Fiberglass T-top, safety and test equipment.

YPB#: PB_SKT_SX2550_F300XCB_07-18-23_BAY



Engine: Yamaha F300XCB

Boat: Skeeter SX2550

Configuration: Single

Test Date: 18-Jul-2023



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.5	1.3	4.06
1500	7.2	2.3	3.16
2000	8.7	4.0	2.17
2500	11.6	5.4	2.14
3000	16.4	6.6	2.47
3500	30.4	8.2	3.69
4000	34.9	11.1	3.15
4500	40.3	14.5	2.78
5000	44.4	18.8	2.37
5500	48.8	24.5	1.99
6050	52.5	26.3	2.00
0-20 MPH: 5.17 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.