PERFORMANCE BULLETIN

Boat Manufactured By:

JUPITER

1103 12th Avenue East • Palmetto, FL 34221

(941) 729-5000

www.jupitermarine.com



JUPITER 26FS

Length	26' 5"
Beam	8' 8"
Dry Weight (Boat Mfr. Pub)	5,460 lbs
Maximum HP	450 hp
Fuel Capacity	150 gal
Weight as Tested	6,324 lbs

LF200XSA2 / F200XSA2

Horsepower	200 hp
Induction	EFI/VCT/DOHC
Displacement	2.8L
Weight (Estimated)	525 - 525 lbs
Gear Ratio	1.86:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3

PROPELLER(S)

Series	Reliance
Diameter x Pitch	13-3/4 x 19
Yamaha Part #	68G-45974-20-00 / 68F-45974-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	71° F / 70° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 120 gallons of fuel, 3 batteries, safety and test equipment.

YPB#: PB_JUP_26FS_TW_LF200XSA2_4-16-24_OCC

Engine: *Yamaha LF200XSA2 / F200XSA2*

Boat: *Jupiter 26FS*

Configuration: *Twin*

Test Date: *16-Apr-2024*



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.4	1.8	3.06
1500	7.7	2.9	2.66
2000	9.1	4.9	1.86
2500	10.9	7.7	1.41
3000	18.3	10.3	1.79
3500	**27.9**	**11.9**	**2.35**
4000	34.6	15.9	2.18
4500	39.7	20.8	1.91
5000	44.7	28.1	1.59
5500	50.7	36.4	1.39
6000	**53.4**	**41.2**	**1.29**

0-20 MPH: 6.14 seconds

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.