

Boat Manufactured By:



One Skeeter Road • Kilgore, TX

(903) 984-0541

www.skeeterboats.com

SKEETER SX2350

Length	22' 9"
Beam	8' 5"
Dry Weight (Boat Mfr. Pub)	3,075 lbs
Maximum HP	250 hp
Fuel Capacity	55 gal
Weight as Tested	4,646 lbs

F250XB

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	551 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15 x 20
Yamaha Part #	6CE-45932-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	83° F / 90° F
Elevation (in feet above sea level)	375'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 50 gallons of fuel, 4 batteries, 2 people, 12" Hydraulic Jackplate, 36 volt trolling motor, safety and test equipment.

YPB#: PB_SKT_SX2350_F250XB_07-19-23_BAY



Engine: Yamaha F250XB

Boat: Skeeter SX2350

Configuration: Single

Test Date: 19-Jul-2023



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.1	1.4	3.74
1500	6.8	2.3	3.02
2000	8.4	3.9	2.17
2500	14.2	5.5	2.55
3000	27.4	6.7	4.08
3500	32.8	9.0	3.65
4000	37.9	12.2	3.10
4500	43.0	15.1	2.86
5000	48.2	20.4	2.37
5500	53.2	23.2	2.29
5900	55.5	24.5	2.27
0-20 MPH: 5.26 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.