

Boat Manufactured By:



1392 Rimmel Dam Rd. • Malvern, AR 72104

(501) 566-1525

www.verandamarine.com

VERANDA VX25RCT

Length	25' 0"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	3,600 lbs
Maximum HP	450 hp
Fuel Capacity	50 gal
Pontoon # / Diameter	3 / 27"
Weight as Tested	4,956 lbs

F300XSB

Horsepower	300 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	611 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#4
------------------------	----

PROPELLER(S)

Series	Saltwater Series II
Diameter x Pitch	15-1/2 x 17
Yamaha Part #	6CE-45978-20-00
Propeller Material	Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	80° F / 75° F
Elevation (in feet above sea level)	299'
Wind Velocity	0-5 MPH

COMMENTS

Test weight includes 35 gallons of fuel, 2 batteries, 2 people, tower, safety and test equipment.

YPB#: PB_VER_VX25RCT_F300XSB_05-15-24_PNT



Engine: Yamaha F300XSB

Boat: Veranda VX25RCT

Configuration: Single

Test Date: 15-May-2024



PERFORMANCE DATA

RPM	MPH	GPH	MPG
1000	5.3	1.3	4.02
1500	7.4	2.1	3.58
2000	10.6	3.4	3.08
2500	16.3	4.6	3.52
3000	20.0	5.9	3.38
3500	25.0	8.1	3.07
4000	29.7	11.6	2.55
4500	35.1	15.4	2.28
5000	40.4	19.4	2.08
5500	44.8	25.0	2.08
5850	46.8	26.2	1.79
0-20 MPH: 4.26 seconds			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.